


Discharge Ratings and Shifts

A. Thomas Ruby III Indiana/Kentucky Water Science Center

Stage/Discharge Relationship



What is needed for an Stage/Discharge site?


Site Selection!!!!


- Site is relatively parallel and uniform
- Near the region of max velocity free from any boundary effects
- Stream is straight for 300ft or 5-10 channel widths
- Located 5-10 channel widths US or DS of any tributary
- Total flow is confined to 1 channel
- Streambed is not subject to scour and fill
- Able to measure discharge at all stages
- Easily accessible for installation and O&M
- Free from air entrainment



Data Collection


- Compute discharge from stage and cross-section area
- Q = VA
 - A = WX









Stage-discharge relations are often referred to as "Ratings".




Discharge measurements must be made throughout the entire range of stage to accurately define a rating.




A computer interpolates the stage discharge values between the defined points on the rating.




Discharge measurements are used to develop rating curves



Discharge must be measured at all stages



Ratings are never that simple!






Rating for Discharge (DCP) (cfs)

RATING ID: 41.0 TYPE: stage-discharge EXPANSION: logarithmic


OFFSET: 0.00

EXPANDED RATING TABLE


Gage							D	DIFF IN Q			
height,	,	Di	Discharge (cfs)					PER			
feet	.00	.01	.02	.03	.04		.09	.1 UNITS			
0.30	1.8*	1.8	1.9	2.0	2.1		2.5	0.80			
0.40	2.6	2.7	2.8	2.9	2.9		3.4	0.90			
0.50	3.5*	3.6	3.8	3.9	4.1		4.9	1.6			
0.60	5.1	5.2	5.4	5.6	5.8		6.7	1.9			
0.70	7.0*	7.2	7.6	7.9	8.2		9.9	3.3			
0.80	10.3*	10.7	11.2	11.7	12.1		14.7	5.0			
0.90	15.3*	15.8	16.4	16.9	17.5		20.6	5.9			








Rating for Discharge (DCP) (cfs)








Rating for Discharge (DCP) (cfs)

EXPANSION: logarithmic

TYPE: stage-discharge

RATING ID: 41.0





Here is how to read a "rating table".

STATION NUMBER Rating for Discharge (DCP) (cfs) RATING ID: 41.0 TYPE: stage-discharge EXPANSION: logarithmic OFFSET: 0.00 EXPANDED RATING TABLE Gage DIFF IN Q height, Discharge (cfs) PER feet .00 .0409 .01 .02 .03 .1 UNITS 0.30 1.8* 1.8 1.9 2.0 2.1 2.5 0.80 0.40 2.6 2.7 2.8 2.9 2.9 3.4 0.90 3.5* 3.6 3.8 3.9 4.1 4.9 0.50 1.6 5.1 5.2 5.4 5.6 5.8 6.7 0.60 1.9 0.70 7.0* 7.2 7.6 7.9 8.2 9.9 3.3 0.80 10.3* 10.7 11.2 11.7 12.1 14.7 5.0 0.90 15.3* 15.8 16.4 16.9 17.5 20.6 5.9



Here is how to read a "rating table".


```
STATION NUMBER
                 Rating for Discharge (DCP) (cfs)
      RATING ID: 41.0
                  TYPE: stage-discharge
                                   EXPANSION: logarithmic
OFFSET: 0.00
                  EXPANDED RATING TABLE
Gage
                                             DIFF IN Q
height,
                Discharge (cfs)
                                               PER
feet
               .01 (.02)
        .00
                           .03
                                 .04 ....
                                          .09
                                               .1 UNITS
               1.8
       1.8*
                    1.9 2.0 2.1 .... 2.5 0.80
0.30
               2.7
                    2.8
                          2.9
0.40
        2.5
                                2.9 .... 3.4
                                                0.90
0.50
        3.5*
              3.6 3.8 3.9 4.1 .... 4.9
                                                1.6
0.60
       5.1 5.2 5.4 5.6 5.8 .... 6.7
                                                1.9
0.70
       7.0* 7.2 7.6 7.9 8.2 .... 9.9
                                                3.3
0.80
             10.7 11.2 11.7
       10.3*
                               12.1 .... 14.7
                                                5.0
0.90
       15.3*
             15.8
                   16.4 16.9
                               17.5 .... 20.6
                                                5.9
```



Here is how to read a "rating table".

```
STATION NUMBER
                Rating for Discharge (DCP) (cfs)
      RATING ID: 41.0
                  TYPE: stage-discharge
                                   EXPANSION: logarithmic
OFFSET: 0.00
                  EXPANDED RATING TABLE
Gage
                                             DIFF IN O
height,
                Discharge (cfs)
                                               PER
feet .00
               .01 (.02)
                                 .04 ....
                           .03
                                          .09
                                               .1 UNITS
0.30 1.8* 1.8
                          2.0 2.1 .... 2.5 0.80
0.40
       2.6
              2.7
                          2.9 2.9 .... 3.4 0.90
0.50
      3.5*
              3.6
                    3 8
                          3.9 4.1 .... 4.9
                                                1.6
                    (5.4) 5.6 5.8 .... 6.7 1.9
0.60
       5.1
0.70
       7.0* 7.2
                          7.9
                                8.2 .... 9.9
                                                3.3
0.80
      10.3*
             10.7
                   11.
                       Gage Height = 0.62 feet
0.90
      15.3*
             15.8
                       Discharge = 5.4 cubic feet per sec
```

Control







Section Control

Rock Riffle

Weir


Beaver Dam





Section Control


Identified by a break in the water surface downstream from the gage.





Channel Control


Contained within the normal banks of the channel







Overbank Control

Flow into the floodplain






The shape of a rating is controlled by the channel and it's features.




Temporary changes to the control dictate shifts





Since gage control conditions change, the stagedischarge relations must be adjusted.



Determination of shift from discharge measurement

Form 9-275G (Sep. 2000)		U.S. Ge WATER RI DISCHARGE GAGE IN	JEVE VISIO	ON TAND Comp.by					
Sta. No									
Sta. Name									
Date	,20	Party							
							Disch		
Vethod		No. secs		_ G. H. change		nge	in ;	hrs	
		Horiz. angle coef							
Weter Type							ft. above bottom or	fwl	
Rating used									
vieas. plots	%	% diff. from rating no				Indicated sh	ift		
	GAGE R	EADINGS					ected: waterqualit	y,	
Time			Inside	Outs	ide	sediment, bio	ological, other		
						ļ <u>.</u>			
							nts documented o		
Start							eets: water qualit ge, other		
	ļ .								
	1					Rain gage se	rviced/calibrated _		
	!			-		gaga sa			
						Weather:			
Finish						Air Temp.	°C at		
							*Cat		
Weighted MGH	 					1	ain found		
GH correction	 						at		
CorrectMGH	 			 	\neg	Correct			
Measurement rai conditions: Flow Cross section:	ted excellent	(2%), good (5%					ostr., downstr. of ga on following		
					De:				
Gage operating:					-	noved			
Battery voltage:					_		rte /n	منہ	
subble-gage pre Extreme-GH indi			, cine , mir					A11.	
						· ·	. HWM elev		
JSG checked: -MAAinside/outs		nneight on Stic	^	— r	. e	770 V	. ITYYW 6/6V		
Control:									
Control:									
Control:									
Remarks:		depth at c	ontrol _			=	ft., rated		
Remarks:		depth at c					. ft., ratedshe		

Compute percent difference from rating:

Compute shift:

Example:

 $Q_{\text{measured}} = 7.5 \text{ ft}^3/\text{s}$

 $GH_{Rating} - GH_{Q}$

×100%


Gage height (GH_Q)= 0.89 ft

Gage height from rating $(GH_{Rating}) = 0.95 \text{ ft}$

Computed shift = +0.06 ft

					EXPANDED RA	TING TABLE				
Gage		_								
height,			ischarge (ci			*	PRECISION)			
feet	.00	.01	.02	.03	.04	.05	.06	.07	.08	.09
0.10			0.04*	0.07	0.11	0.15	0.19	0.24	0.29	0.34
0.20	0.39	0.44	0.50	0.56	0.62	0.68	0.75	0.81	0.88	0.95
0.30	1.0	1.1	1.2	1.2	1.3	1.4	1.5	1.5	1.6	1.7
0.40	1.8	1.9	1.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6
0.50	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5
0.60	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.5
0.70	4.6	4.7	4.9	5.0	5.1	5.2	5.3	5.4	5.5	5.6
0.80	5.7	5.9	6.0	6.1	6.2	6.3	6.4	6.6	6.7	6.8
0.90	6.9	7.0	7.2	7.3	7.4	7.5	7.6	7.8	7.9	8.0
1.00	8.1	8.3	8.4	8.5	8.6	8.8	8.9	9.0	9.2	9.3
1.10	9.4	9.5	9.7	9.8	9.9	10.1	10.2	10.3	10.5	10.6
1.20	10.7	10.9	11.0	11.1	11.3	11.4	11.6	11.7	11.8	12.0
1.30	12.1	12.2	12.4	12.5	12.7	12.8	13.0	13.1	13.2	13.4
1.40	13.5	13.7	13.8	14.0	14.1	14.3	14.4	14.5	14.7	14.8
1.50	15.0	15.1	15.3	15.4	15.6	15.7	15.9	16.0	16.2	16.3
1.60	16.5	16.6	16.8	16.9	17.1	17.3	17.4	17.6	17.7	17.9
1.70	18.0	18.2	18.3	18.5	18.7	18.8	19.0	19.1	19.3	19.4
1.80	19.6	19.8	19.9	20.1	20.2	20.4	20.6	20.7	20.9	21.1
1.90	21.2	21.4	21.5	21.7	21.9	22.0	22.2	22.4	22.5	22.7

Interpretation of a positive computed shift.



The gage height $(GH_O) = 0.89$ ft.

For this gage height the rating table indicates that the discharge should be 6.8 ft³/s.

Discharge measured = $7.5 \text{ ft}^3/\text{s}$.

The rating table says 7.5 ft 3 /s is associated with a gage height (GH_{Rating}) of 0.95 ft .


The computed shift = +0.06 ft.

The control scoured ~0.06 ft.

GH_{rating}=0.95ft GH_Q=0.89 ft



Interpretation of a negative computed shift. The gage height (GH_Q) = 0.89 ft.




For this gage height the rating table indicates that the discharge should be $6.8 \text{ ft}^3/\text{s}.$

Discharge measured = $5.7 \text{ ft}^3/\text{s}$.

The rating table says 5.7 ft³/s is associated with a gage height (GH_{Rating}) of 0.80 ft.


The computed shift = -0.09 ft.


The control filled ~0.09 ft.






One reason negative shifts occur is due to fill on the control.







One reason negative shifts occur is due to fill on the control.





One reason negative shifts occur is due to fill on the control.





Computed shift values and the rating curve.






Shift curves and the rating curve.






Variable Shift Diagram (V-diagram).





Proration of shift curves.






Shift curves, the rating, and the gage height record.










Development of shift curves.





Application of shift curves to gage height record.





How does this translate to the data on the web?


Seamlessly

If a shift is added correctly, the web shows the data with the corrected values.


If a shift wasn't applied the measurement will look like it'd not in line with the data.




Example of either a shift applied or no shift needed




Example of either a shift applied or no shift needed



Example of either a shift not applied but needed



Example of either a shift not applied but needed



How can you determine if a shift was added?

This station managed by the Louisville District Office. **Output format Available Period Available Parameters** Graph All 9 Available Parameters for this site OGraph w/ stats ✓ 00065 Gage height 2014-02-05 2014-06-05 OGraph w/o stats ✓ 00060 Discharge 2007-10-01 2014-06-05 OGraph w/ (up to 3) parms □ 00045 Precipitation 2014-02-05 2014-06-05 O Table ☐ 70969 DCP battery voltage O Tab-separated 2014-04-29 2014-06-05 00010 Temperature, water 2007-10-01 2014-06-05 □ 00300 Dissolved oxygen 2007-10-01 2014-06-05 □ 00400 pH 2007-10-01 2014-06-05 ☐ 00095 Specific cond at 25C 2007-10-01 2014-06-05 ☐ 63680 Turbidity, Form Neph 2011-06-06 2014-06-04 Summary of all available data for this site Instantaneous-data availability statement



How can you determine if a shift was added?

This station managed by the Louisville District Office. **Output format Available Period Available Parameters** Graph All 9 Available Parameters for this site OGraph w/ stats ✓ 00065 Gage height 2014-02-05 2014-06-05 OGraph w/o stats ✓ 00060 Discharge 2007-10-01 2014-06-05 OGraph w/ (up to 3) parms □ 00045 Precipitation 2014-02-05 2014-06-05 O Table ☐ 70969 DCP battery voltage O Tab-separated 2014-04-29 2014-06-05 □ 00010 Temperature, water 2007-10-01 2014-06-05 ☐ 00300 Dissolved oxygen 2007-10-01 2014-06-05 □ 00400 pH 2007-10-01 2014-06-05 ☐ 00095 Specific cond at 25C 2007-10-01 2014-06-05 ☐ 63680 Turbidity, Form Neph 2011-06-06 2014-06-04 Summary of all available data for this site Instantaneous-data availability statement



DESCRIPTION:

Latitude 39°04'47", Longitude 84°41'07" NAD83 Boone County, Kentucky, Hydrologic Unit 05090203 Drainage area: 4.03 square miles

Datum of gage: 759.08 feet above NGVD29.

AVAILABLE DATA:

Data Type	Begin Date	End Date	Count
Current / Historical Observations (availability statement)	2007-10-01	2014-06-05	
<u>Daily Data</u>			
Temperature, water, degrees Celsius	2001-03-07	2010-09-30	9651
Discharge, cubic feet per second	1999-04-09	2014-06-04	5526
Specific conductance, water, unfiltered, microsiemens per centimeter at 25 degrees Celsius	2001-03-07	2010-09-30	9202
Dissolved oxygen, water, unfiltered, milligrams per liter	2001-03-07	2010-09-30	7722
pH, water, unfiltered, field, standard units	2001-03-07	2010-09-30	8702
Turbidity, water, unfiltered, monochrome near infra-red LED light, 780-900 nm, detection angle 90 +-2.5 degrees, formazin nephelometric units (FNU)	2001-03-07	2003-06-17	1044
Daily Statistics			
Temperature, water, degrees Celsius		2010-09-30	
Discharge, cubic feet per second	1999-04-09	2013-09-30	5279
Specific conductance, water, unfiltered, microsiemens per centimeter at 25 degrees Celsius	2001-03-07	2010-09-30	3067
Dissolved oxygen, water, unfiltered, milligrams per liter	2001-03-07	2010-09-30	2574
pH, water, unfiltered, field, standard units	2001-03-07	2005-08-02	1240
Turbidity, water, unfiltered, monochrome near infra-red LED light, 780-900 nm, detection angle 90 +-2.5 degrees, formazin nephelometric units (FNU)	2001-03-07	2003-06-17	368
Monthly Statistics			
Temperature, water, degrees Celsius	2001-03	2010-09	
Discharge, cubic feet per second	1999-04	2013-09	
Specific conductance, water, unfiltered, microsiemens per centimeter at 25 degrees Celsius	2001-03	2010-09	
Dissolved oxygen, water, unfiltered, milligrams per liter	2001-03	2010-09	
pH, water, unfiltered, field, standard units	2001-03	2005-08	
Turbidity, water, unfiltered, monochrome near infra-red LED light, 780-900 nm, detection angle 90 +-2.5 degrees, formazin nephelometric units (FNU)	2001-03	2003-06	
Annual Statistics			
Temperature, water, degrees Celsius	2001	2010	
Discharge, cubic feet per second	1999	2013	
Specific conductance, water, unfiltered, microsiemens per centimeter at 25 degrees Celsius	2001	2010	
Dissolved oxygen, water, unfiltered, milligrams per liter	2001	2010	
pH, water, unfiltered, field, standard units	2001	2005	
Turbidity, water, unfiltered, monochrome near infra-red LED light, 780-900 nm, detection angle 90 +-2.5 degrees, formazin nephelometric units (FNU)	2001	2003	
Peak streamflow	2000-01-03	2011-09-26	11
Field measurements	1999-04-08	2014-05-09	104
Additional Data Sources	Begin Date	End Date	Count
Instantaneous-Data Archive **offsite**	1999-04-09	2007-09-30	390562
Annual Water-Data Report (pdf) **offsite**	2006	2013	8



DESCRIPTION:

Latitude 39°04'47", Longitude 84°41'07" NAD83 Boone County, Kentucky, Hydrologic Unit 05090203 Drainage area: 4.03 square miles

Datum of gage: 759.08 feet above NGVD29.

AVAILABLE DATA:

Data Type	Begin Date	End Date	Count
Current / Historical Observations (availability statement)	2007-10-01	2014-06-05	
<u>Daily Data</u>			
Temperature, water, degrees Celsius	2001-03-07	2010-09-30	9651
Discharge, cubic feet per second	1999-04-09	2014-06-04	5526
Specific conductance, water, unfiltered, microsiemens per centimeter at 25 degrees Celsius	2001-03-07	2010-09-30	9202
Dissolved oxygen, water, unfiltered, milligrams per liter	2001-03-07	2010-09-30	7722
pH, water, unfiltered, field, standard units	2001-03-07	2010-09-30	8702
Turbidity, water, unfiltered, monochrome near infra-red LED light, 780-900 nm, detection angle 90 +-2.5 degrees, formazin nephelometric units (FNU)	2001-03-07	2003-06-17	1044
Daily Statistics			
Temperature, water, degrees Celsius	2001-03-07	2010-09-30	3218
Discharge, cubic feet per second	1999-04-09	2013-09-30	5279
Specific conductance, water, unfiltered, microsiemens per centimeter at 25 degrees Celsius		2010-09-30	
Dissolved oxygen, water, unfiltered, milligrams per liter	2001-03-07	2010-09-30	2574
pH, water, unfiltered, field, standard units		2005-08-02	1240
Turbidity, water, unfiltered, monochrome near infra-red LED light, 780-900 nm, detection angle 90 +-2.5 degrees, formazin nephelometric units (FNU)	2001-03-07	2003-06-17	368
Monthly Statistics			
Temperature, water, degrees Celsius	2001-03	2010-09	
Discharge, cubic feet per second	1999-04	2013-09	
Specific conductance, water, unfiltered, microsiemens per centimeter at 25 degrees Celsius	2001-03	2010-09	
Dissolved oxygen, water, unfiltered, milligrams per liter	2001-03	2010-09	
pH, water, unfiltered, field, standard units	2001-03	2005-08	
	2001-03	2003-06	
Annual Statistics			
Temperature, water, degrees Celsius	2001	2010	
Discharge, cubic feet per second	1999	2013	
Specific conductance, water, unfiltered, microsiemens per centimeter at 25 degrees Celsius	2001	2010	
Dissolved oxygen, water, unfiltered, milligrams per liter	2001	2010	
pH, water, unfiltered, field, standard units	2001	2005	
Turbidity, water, unfiltered, monochoose near infra-red LED light, 780-900 nm, detection angle 90 +-2.5 degrees, formazin nephelometric units (FNU)	2001	2003	
Peak streamflow		2011-09-26	11
Field measurements	1999-04-08	2014-05-09	104
Additional Data Sources	Begin Date	End Date	Count
Instantaneous-Data Archive **offsite**	1999-04-09	2007-09-30	390562
Annual Water-Data Report (pdf) **offsite**	2006	2013	8



Streamflow Measurements for the Nation USGS 03260100 ELIJAHS CREEK @ ELIJAHS CREEK RD NR HEBRON, KY Boone County, Kentucky Hydrologic Unit Code 05090203 Latitude 39°04'47", Longitude 84°41'07" NAD83 Drainage area 4.03 square miles Gage datum 759.08 feet above NGVD29 Output formats HTML table with channel data ITML table without channel data Tab-separated data with channel data Graph of data Reselect output format Stream flow (ft²/s) \$ Gage Height (ft) \$ Shift Adj. (ft) ¢ GH Change (ft) 0 Meas. Duratio (hr) Flow Adjust. \$ % Diff. © Control Date Who 104 2014-05-09 08:16:30 EDT JGT/BLM USGS 0.92 1.42 4.1 0.00 -23.3 0.00 0.50 FATR MEAS 103 2014-04-16 17:41 EDT MKL USGS 2,88 1,53 4.1 -0.04 -1.4 0.00 0.50 POOR MALT MEAS MEAS 102 2014-02-18 14:20:30 30.2 0.00 -90.2 0.14 0.50 POOR SICE 9.73 -0.06 -3.7 -0.01 0.75 FAIR LGDB MEAS -0.06 0.0 0.02 FAIR LGDB 100 2013-11-01 09:23:30 13.9 99 2013-08-22 08:43 EDT SMM/MKL USGS 0.11 1.39 4.1 -0.06 0.0 FAIR MDDB MEAS MEAS USGS -0.04 2.1 98 2013-07-02 08:06:30 EDT 7.80 1.64 4.1 GOOD CLER EDT MKL/ATR USGS -0.05 -2.6 0.00 0.60 POOR CLER MEAS 97 2013-04-30 17:55:30 1.14 1.47 4.1 MEAS 96 2013-01-30 18:24:30 EST USGS 19.1 1.87 4.1 -0.12 -1.0 0.00 0,40 FAIR CLER 95 2012-10-15 17:05 EDT MKL/SJS USGS 0.73 -0.04 7.4 0.00 0.10 POOR LGDB MEAS 94 2012-10-15 15:59 MEAS 0.00 0.50 POOR MDDB 93 2012-09-07 07:54 USGS 0.70 1.40 4.1 -0.01 2.9 0.00 0.25 POOR MALT MEAS MEAS 92 2012-07-10 16:34 EDT 1.34 4.1 -0.04 42.9 0.00 0.01 POOR LGDB 91 2012-07-10 16:28:51 EDT DJS USGS 0.010 -0.04 42.9 0.00 0.04 POOR LGDB MEAS Yes 1.34 4.1 MEAS MKL/RWT USGS 0.14 -0.06 100 0.00 0.12 90 2012-06-14 13:57:30 EDT 1.38 4.1 POOR LGDB MEAS MEAS 89 2012-06-14 13:26:16 EDT MKL USGS 0.043 1.38 4.1 -0.06 -33.8 0.00 0.43 POOR LGDB 88 2012-04-05 17:45:30 EDT ATR/MK USGS 0.73 4.1 -0.01 7.4 0.00 0.08 POOR CLER 87 2012-04-05 17:40:49 EDT BLM 0.53 -0.01 -22.1 0.00 0.15 POOR CLER MEAS 86 2012-01-10 17:14:43 USGS 0.77 -0.01 -22.2 0.00 0.07 POOR CLER MEAS 85 2012-01-10 17:07:09 EST MKL USGS 1.02 1.42 4.1 -0.01 2.9 0.00 0.08 POOR CLER MEAS EDT USGS 0.74 -0.03 68.2 0.00 0.17 POOR MDDB MEAS 84 2011-10-04 12:11:57 1.40 4.1

1,40

1.44

4.1

4

-0.03 9.1

0.03 -2.1

0.00

0.14

POOR MDDB

FAIR CLER

MEAS MEAS



83 2011-10-04 11:55:45

82 2011-06-30 16:42:03

EDT

EDT

Yes

ZH

DJR

USGS


USGS

0.48

0.92

Streamflow Measurements for the Nation USGS 03260100 ELIJAHS CREEK @ ELIJAHS CREEK RD NR HEBRON, KY Boone County, Kentucky Hydrologic Unit Code 05090203 Latitude 39°04'47", Longitude 84°41'07" NAD83 Drainage area 4.03 square miles Gage datum 759.08 feet above NGVD29 **Output formats** HTML table with channel data TML table without channel data Tab-separated data with channel data aph of data Stream flow (ft²/s) \$ GH Change (ft) Meas. Duratio (hr) Flow Adjust. Adj. \$ 96 Diff. © Control 104 2014-05-09 08:16:30 FDT JGT/BLM USGS 0.92 1.42 4.1 0.00 -23.3 0.00 0.50 MEAS 103 2014-04-16 17:41 EDT MKL USGS 2,88 1,53 4.1 -0.04 -1.4 0.00 0.50 POOR MALT MEAS MEAS 102 2014-02-18 14:20:30 30.2 2.80 4.1 0.00 -90.2 0.14 0.50 POOR SICE 101 2013-11-19 16:23 EST USGS 9.73 1.70 4.1 -0.06 -3.7 -0.01 0.75 FAIR LGDB Stream Shift GH Gage Meas. Meas. ≎ Measurement 6 flow Rating 0 Measuring _ **\$** Height ≎ Adj. ≎ % Change ≎ **Duration ♦** Time Control [♦] **Datum** Used? Who (ft^3/s) (ft) No. (ft) Diff. (ft) (hr) Rated Agency :30 EDT JGT/BLM USGS 0.92 1.42 4.1 0.00 -23.3 0.00 0.50 **FAIR** Yes EDT MKL USGS 2.88 1.53 -0.04 -1.4 0.00 0.50 POOR MALT Yes 4.1 :30 **USGS** 2.80 0.50 EST Yes MKL 30.2 4.1 0.00 -90.2 0.14 POOR SICE **EST** MKL USGS 9.73 0.75 FAIR LGDB Yes 1.70 4.1 -0.06 -3.7 -0.01 :30 EDT Yes MKL/BLM **USGS** 13.9 1.75 4.1 -0.06 0.0 0.02 0.50 FAIR LGDB **EDT** Yes SMM/MKL USGS 0.11 1.39 4.1 -0.06 0.0 FAIR MDDB :30 EDT SMM/MKL USGS 7.80 1.64 4.1 -0.04 2.1 GOOD CLER Yes :30 EDT Yes MKL/ATR **USGS** 1.14 1.47 4.1 -0.05 -2.6 0.00 0.60 POOR CLER :30 EST Yes SMM/ATR USGS 19.1 1.87 4.1 -0.12 -1.0 0.00 0.40 FAIR CLER EDT Yes MKL/SJS USGS 0.73 1.43 4.1 -0.04 7.4 0.00 0.10 POOR LGDB EDT MKL/BLM **USGS** 0.44 1.43 4.1 -0.04 -35.3 0.00 0.50 POOR MDDB Yes EDT MKL **USGS** 0.70 1.40 4.1 -0.01 2.9 0.00 0.25 POOR MALT Yes







Questions?

